



Ordering Information

Catalog No.	Finishes	Track Mountings	Luminaires	Lamp
28B10EWH 28B10EBK 28B10EAL	Matte White Matte Black Metallic Aluminum	All ProSpec® Track Systems. DO NOT USE with any other mounting accessories, stem mounted Radius® Track, Lytespan® Track systems, or ATOM®. Can be wall mounted.	Use one of: 8317 83W7 8318	100W Ceramic Metal Halide

Features

- Housing:** .10" thick extruded aluminum body with die cast end caps.
- Track Attachment Fitting:** Molded polycarbonate; rotates into track.
- Ground Clip:** Ensures proper grounding of module.
- Safety Locking Lever:** Locks and supports module in track.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Power Receptacle:** 5kv rated, insulated. Accepts power connector from fixture.
- Integral Track Groove:** To mount PowerArc™ Modular spots and wall wash fixtures.

Electrical

Electronic Ballast

Input Voltage: 120V, 60Hz
Power Factor: High
Input Power: 110W
Max. Input Current: 0.90A
Total Harmonic Distortion: <15%
ANSI Code: M90 or M140

Do not use on dimming circuit.

Finish

All painted finishes are baked enamel.

Labels

UL, cUL

Patents

Products shown here are protected by applicable patents and patents pending.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • B1108